

ORDERING GUIDE FOR THE ELIMINATOR SPL ACTUATOR

Ordering Information

Base No. (Capacity)	Unit Mounting Option	Motor Position	Precision/Lead Accuracy**
SPL201 (1,000 lbf)	MB: Bottom Mount	1, 3, 4	C: .0005 in/ft .003 in. Backlash
SPL302 (2,000 lbf)	FF: Front Flange	0 = In-Line	X: Standard
SPL304 (4,000 lbf)	MF: Foot Mount		
SPL404 (4,000 lbf)	TF: Front Trunnion		
SPL406 (6,000 lbf)			
SPL508 (8,000 lbf)			
SPL516 (16,000 lbf)			
SPL618 (18,000 lbf)			
SPL625 (25,000 lbf)			

Std. Stroke Length*	Rod End Option ****	Gearbelt Reduction	N.C. Switch Qty ****
06: 6 in.	E: Female Eye	00: In-Line/Direct Coupled	0, 1, 2, 3, etc.
12: 12 in.	F: Female Thread	10: 1:1	
18: 18 in.	A: Self-Aligning Coupler**	20: 2:1	
24: 24 in.	M: Male Thread		
30: 30 in.	S: Spherical Rod Eye		
36: 36 in.			
42: 42 in.			
48: 48 in.			

Configuration	Switch Type
L: In-Line	A: Hall Sourcing PNP
U: Parallel Offset	B: Hall Sinking NPN
	C: Reed
	X: No Switches

For custom stroke lengths, contact EDrive.

* Standard Stroke Lengths

SPL201 - 0.0005 in/ft, 0.003 in. Backlash

SPL302 – SPL304 stroke lengths up to 36 in.

SPL404 – SPL406 stroke lengths up to 42 in.

SPL508 – SPL625 stroke lengths up to 48 in.

** Self-Aligning Coupler

Not available for SPL625

*** Precision/Lead Accuracy

SPL201-0.0005 in/ft, 0.003 in. Backlash

**** IP69K Exceptions

Self-Aligning Coupler and Spherical Rod Ends not rated

Sealed Limit Switches, IP65 rated