



PRODUCT ORDERING GUIDE

Eliminator Series HD

Custom products are available.

Contact sales@edriveactuators.com with your requirements.

BASE NUMBER				OPTIONS				SPECIAL									
H	D			-			-			-							
Base No. (Capacity) HD201 (1,000 lbf) HD302 (2,000 lbf) HD304 (4,000 lbf) HD404 (4,000 lbf) HD406 (6,000 lbf) HD508 (8,000 lbf) HD516 (16,000 lbf) HD518 (18,000 lbf) HD625 (25,000 lbf)				Unit Mounting Option MB: Bottom Mount FF: Front Flange MF: Foot Mount TF: Front Trunnion TR: Rear Trunnion				Motor Position 1, 2, 3, 4 0 = In-Line 				Custom Length (in) 00.00					
Std. Stroke Length* 06: 6 in. 12: 12 in. 18: 18 in. 24: 24 in. 30: 30 in. 36: 36 in. 42: 42 in. 48: 48 in.				Rod End Option E: Female Eye F: Female Thread A: Self-Aligning Coupler M: Male Thread S: Spherical Rod Eye				Gearbelt Reduction 00: In-Line/Direct Coupled 10: 1:1 20: 2:1				Precision/Lead Accuracy** A: .002 in/ft Zero Backlash B: .0005 in/ft Zero Backlash X: Standard					
				Configuration L: In-Line U: Parallel Offset				Switch Type A: Hall Sourcing PNP B: Hall Sinking NPN C: Reed D: Switch Track / No Switches X: Solid Cover / No Switches				N.C. Switch Qty 0, 1, 2, 3, etc.					
								N.O. Switch Qty 0, 1, 2, 3, etc.									

* HD201 is available with stroke lengths up to 12 in.
 HD302 – HD304 are available with stroke lengths up to 36 in.
 HD404 – HD406 are available with stroke lengths up to 42 in.
 HD508 – HD625 are available with stroke lengths up to 48 in.
 ** HD201 – Std. Precision/Lead Accuracy is 0.0005 in/ft, Zero Backlash
 ** HD302, HD404 – Zero Backlash not available

For applications support contact us today.

sales@edriveactuators.com

FB6146

EDrive Actuators, Inc.
 385 Stamm Rd.
 Newington, CT 06111

Website: edriveactuators.com
 Phone: 1.860.953.0588
 Fax: 1.860.953.0496

© 2021 all rights reserved