


ORDERING GUIDE FOR THE TAC VP ACTUATOR

Ordering Information

| V | P | | | | - | | | - | | | - | | | - | | | | | |
|----------------------------|---|--|--|--|-----------------------------|--|--|---|--|---|---|--|--|---|-------------------------|--|--|--|--|
| Base No. (Capacity) | | | | | Unit Mounting Option | | | | | Motor Position | | | | | N.C. Switch Qty* | | | | |
| VP204 (400 lbf) | | | | | MB: Bottom Mount | | | | | 1, 2, 3, 4 | | | | | 0, 1, 2, 3, etc. | | | | |
| VP209 (900 lbf) | | | | | MF: Foot Mount | | | | | 0 = In-Line | | | | | | | | | |
| VP305 (500 lbf) | | | | | FF: Front Flange | | | | |  | | | | | | | | | |
| VP310 (1,000 lbf) | | | | | | | | | | | | | | | | | | | |
| VP320 (2,000 lbf) | | | | | | | | | | | | | | | | | | | |
| Std. Stroke Length | | | | | Rod End Option* | | | | | Gearbelt Reduction | | | | | N.O. Switch Qty* | | | | |
| 6: 6 in. | | | | | E: Female Eye | | | | | 00: In-Line/Direct Coupled | | | | | 0, 1, 2, 3, etc. | | | | |
| 12: 12 in. | | | | | F: Female Thread | | | | | 10: 1:1 | | | | | | | | | |
| 18: 18 in. | | | | | A: Self-Aligning Coupler | | | | | 20: 2:1 | | | | | | | | | |
| 24: 24 in. | | | | | M: Male Thread | | | | | | | | | | | | | | |
| | | | | | S: Spherical Rod Eye | | | | | | | | | | | | | | |
| | | | | | Configuration | | | | | Switch Type | | | | | | | | | |
| | | | | | L: In-Line | | | | | A: Hall Sourcing PNP | | | | | | | | | |
| | | | | | U: Parallel Offset | | | | | B: Hall Sinking NPN | | | | | | | | | |
| | | | | | | | | | | C: Reed | | | | | | | | | |
| | | | | | | | | | | X: No Switches | | | | | | | | | |

For custom stroke lengths, contact EDrive.

* IP69K Exceptions
Self-Aligning Coupler and Spherical Rod Ends not rated
Sealed Limit Switches, IP65 rated