


PRODUCT ORDERING GUIDE

Tac Series LS

Custom products are available.

Contact sales@edriveactuators.com with your requirements.

BASE NUMBER	OPTIONS	SPECIAL
<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 2px;">L</div> <div style="border: 1px solid black; padding: 2px;">S</div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> </div> <div style="display: flex; justify-content: space-between;"> <div style="width: 20%;"> <p>Base Parts No. (Capacity)</p> <p>LS204 (400 lbf)</p> <p>LS209 (900 lbf)</p> <p>LS305 (500 lbf)</p> <p>LS310 (1,000 lbf)</p> <p>LS320 (2,000 lbf)</p> </div> <div style="width: 20%;"> <p>Unit Mounting Option</p> <p>MB: Bottom Mount</p> <p>MF: Foot Mount</p> <p>CR: Rear Clevis**</p> <p>FF: Front Flange**</p> <p>TF: Front Trunnion**</p> <p>TR: Rear Trunnion**</p> </div> <div style="width: 20%;"> <p>Motor Position</p> <p>1, 2, 3, 4</p> <p>0 = In-Line</p>  </div> <div style="width: 20%;"> <p>End Effector/Rod End</p> <p>E: Female Eye</p> <p>F: Female Thread</p> <p>A: Self-Aligning Coupler</p> <p>M: Male Thread</p> <p>S: Spherical Rod Eye</p> </div> <div style="width: 20%;"> <p>Gearbelt Reduction</p> <p>00: In-Line/Direct Coupled</p> <p>10: 1:1</p> <p>20: 2:1</p> </div> <div style="width: 20%;"> <p>Switch Type</p> <p>A: Hall Sourcing PNP</p> <p>B: Hall Sinking NPN</p> <p>C: Reed</p> </div> <div style="width: 20%;"> <p>Custom Length (in)</p> <p>00.00</p> </div> <div style="width: 20%;"> <p>N.C. Switch Qty</p> <p>0, 1, 2, 3, etc.</p> </div> <div style="width: 20%;"> <p>N.O. Switch Qty</p> <p>0, 1, 2, 3, etc.</p> </div> </div>	<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> </div> <div style="display: flex; justify-content: space-between;"> <div style="width: 20%;"> <p>Std. Stroke Lengths*</p> <p>24: 24 in.</p> <p>30: 30 in.</p> <p>36: 36 in.</p> <p>42: 42 in.</p> <p>48: 48 in.</p> <p>54: 54 in.</p> <p>60: 60 in.</p> </div> <div style="width: 20%;"> <p>Configuration</p> <p>L: In-Line</p> <p>U: Parallel Offset</p> </div> </div>	<div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> <div style="border: 1px solid black; width: 20px; height: 20px;"></div> </div>

* LS204 – LS209 are available with stroke lengths up to 36 in.
 LS305 – LS320 are available with stroke lengths from 30 in. to 60 in.
 ** Vertical Mounting Only