



PRODUCT ORDERING GUIDE

Eliminator Series STL

STAINLESS STEEL WITH LOAD CELL

Custom products are available.

Contact sales@edriveactuators.com with your requirements.

BASE NUMBER				OPTIONS						SPECIAL					
S	T	L													
Base Parts No. (Capacity)				Unit Mounting Option			Motor Position			Custom Length (in)					
STL201 (850 lbf)				MB: Bottom Mount			1, 3, 4			00.00					
STL302 (2,000 lbf)				FF: Front Flange			0 = In-Line			Precision/Lead Accuracy					
STL304 (4,000 lbf)				MF: Foot Mount						A: .002 in/ft					
STL404 (4,000 lbf)				TF: Front Trunnion						B: .0005 in/ft					
STL406 (6,000 lbf)				TR: Rear Trunnion			Gearbelt Reduction			N.C. Switch Qty					
STL508 (8,000 lbf)							00: In-Line/Direct Coupled			0, 1, 2, 3, etc.					
STL516 (16,000 lbf)				End Effector/Rod End			10: 1:1			N.O. Switch Qty					
STL518 (18,000 lbf)				E: Female Eye			20: 2:1			0, 1, 2, 3, etc.					
STL625 (25,000 lbf)				F: Female Thread			Switch Type								
				A: Self-Aligning Coupler**			A: Hall Sourcing PNP								
Std. Stroke Lengths*				M: Male Thread			B: Hall Sinking NPN								
06: 6 in.				S: Spherical Rod Eye			C: Reed								
12: 12 in.				Configuration											
18: 18 in.				L: In-Line											
24: 24 in.				U: Parallel Offset											
30: 30 in.															
36: 36 in.															
42: 42 in.															
48: 48 in.															

* STL201 is available with stroke lengths up to 12 in.
 STL301 – STL304 are available with stroke lengths up to 36 in.
 STL404 – STL406 are available with stroke lengths up to 42 in.
 STL508 – STL625 are available with stroke lengths up to 48 in.
 ** Self-Aligning Coupler is not available for STL625